

rocpower®

power your future



Smarttower

Line Interactive,
Sine Wave UPS, Mini Tower

Smarttower

Line-interactive, Sine Wave UPS

The Smarttower series UPS provides high-performance but inexpensive power protection solutions for most business applications with critical file servers, network switches, hubs and small computers.

Features

- AVR Boost and Buck
- Pure Sine Wave Output
- User Friendly LCD Display
- Advanced Battery Management
- Nearly Zero Transfer Time
- 97% High Efficiency in Normal Mode
- Easy Swappable Battery
- Patent RS232 and USB Communication Interfaces

1000T / 1500T



2000T / 3000T



Smarttower	RPT 1000 T	RPT 1500 T	RPT 2000 T	RPT 3000 T
Input - Voltage Window	110/115/120 +/-25%, DIP Switch Selectable			
Frequency	50/60			
Output - Voltage AC Mode	Increase output 15% (input -9%~-25%) or Decrease output 15% (input +9 ~ +25%)			
Voltage Inv. Mode	110/115/120 +3%~-10%			
Frequency	50/60Hz ±0.2%			
Capacity(VA/W)	1000 / 600	1500 / 900	2000 / 1200	3000 / 1800
Wave Form	Sine Wave; <3%(Linear Load)			
Transfer Time	4ms typical			
Autonomy	9 minutes(half load)			
DC Start	Yes			
Battery - Type	Sealed Lead Acid Maintenance Free			
Capacity	12V/7AH	12V/9AH	12V/7AH	12V/9AH
Quantity	2pcs		4pcs	
Voltage	24Vdc		48Vdc	
Recharge Time	2~4 hours to 90%			
Dimensions	6.8"x9.7"x14.5" (173x247x369mm)		6.8"x9.7"x16.8" (173x247x427mm)	
Net Weight	29lbs (13Kg)	33lbs (15Kg)	49lbs (22Kg)	53lbs (24kg)
Outlets	4 NEMA5-15R		6 NEMA5-15R	
Interface Type	Standard RS232/USB Interfaces			
Compatible Platforms	Windows 95/98/NT/2000/XP/Vista			

User-Friendly Design

Can easily be installed by consumer. All units up to 3KVA are supplied with input cables and output sockets as standard.

rocpower® www.rocpower.com



Designed/integrated/assembled in USA using domestic and/or foreign components.

Rocpower is A division of Rocstor. Rocstor is A California company U.S.A.